

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).

Electrically Controlled Single-point Locks and Latches Certified for Canada

COMPANY

dormakaba Canada Inc.

105 Blvd Marcel-Laurin
Saint-Laurent, QC H4N 2M3 Canada

R18481

Cylindrical type Model(s) Solitaire Prox and Solitaire 761, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height, and for use with 20 minute single swinging doors not exceeding 915 mm in width by 2135 mm in height.

Cylindrical type, with 16 mm (5/8 in.) latch bolts, battery operated Model(s) 700 and 800 EHL, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height.

Cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) E-761, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Electrically controlled single point lockset with a 19 mm (3/4 in.) latch bolt "Saflok" Model(s) Quantum MT

Interconnected type, with a 12.7 mm (1/2 in.) latch bolt, battery operated Model(s) Series SAFFIRE LX-I, Model MN302 for use with swinging type fire doors for a 30 minute rating, and suitable for use on wood core doors rated up to 30 min

Interconnected type, with a 12.7 mm (1/2 in.) latch bolt, battery operated Model(s) Series SAFFIRE LX-I, Models MN002, MNM12, MN442, and MN4M2

Interconnected type, with a 12.7 mm (1/2 in.) latch bolt, battery operated Model(s) Saffire Evo LX-I, Saffire Evo LZ-I and Saffire Evo VR-I

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolt, self-powered Model(s) E-PLEX Power Star 2000 and 2400, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) E-660, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) E-770, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) E-790, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) E-PLEX 2000 and 2400, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) PowerPlex 2000 and PowerPlex 2400, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) Solitaire 710 II, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swinging wood doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) Solitaire 710, 850, 950 and E-PLEX 7100, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height, and 20 minute single swinging wood doors not exceeding 915 mm in width by 2135 mm in height.

Mortise and cylindrical type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) Solitare SMART 740, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swinging doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise type and cylindrical type Model(s) EPLEX 7900 Series, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height

Mortise type, with 19 mm (3/4 in.) latch bolts, 6 Vdc battery operated, for use with swinging fire doors "Saflok" Model(s) Concierge RFID, Insync, M Class, M Class 3H, MT RFID, Quantum 2 MT RFID, Quantum 2 RFID, Quantum 3 Adese RFID, Quantum 3 MT RFID, Quantum 4 Adese RFID, Quantum 4 MT RFID, Quantum RFID

Mortise type, with 19 mm (3/4 in.) latch bolts, 6 Vdc battery operated, for use with swinging fire doors Model(s) Gibraltar, Saflok, Saflok 2500, Saflok MT, Saflok V

Mortise type, with 19 mm (3/4 in.) latch bolts, 6 Vdc battery operated, for use with swinging fire doors up to 1/3 hr. Model(s) Insync M Class

Mortise type, with 19 mm (3/4 in.) latch bolts, 6 Vdc battery operated, for use with swinging fire doors up to 1/3 or 3 hr. "Saflok" Model(s) Adese XT

Mortise type, with 19 mm (3/4 in.) latch bolts, 6 Vdc battery operated, for use with swinging fire doors up to 3/4 hr. "Saflok" Model(s) Confidante MT

Mortise type, with 19 mm (3/4 in.) latch bolts, 6 Vdc battery operated, for use with swinging wood, wood core doors for 1/3 hr., composite fire doors up to 1 hr. or hollow metal fire doors up to 3 hr. Model(s) Quantum Pixel RFID Series

Mortise type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) 700 and 800 EHL, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) Confidant RFID, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) E-760, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) M71 and M76, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swing doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) Oracode 610, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and 20 minute single swinging wood doors, not exceeding 915 mm in width by 2135 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, battery operated Model(s) Solitare 1000, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, rated 13.8 Vdc Model(s) ML9000 (Decorative) and Millenium 530, for use with 3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height, and for use with 20 minute single swing doors not exceeding 915 mm in width by 2135 mm in height.

Mortise type, with 19 mm (3/4 in.) latch bolts, rated 13.8 Vdc Model(s) ML9000 (Standard), (Millenium 510), with 3 h hollow metal single swing doors not exceeding 1220 mm in width by 2440 mm in height.

Mortise with 19 mm (3/4 in.) latch bolt and cylindrical type with 1/2 in. (12.7 mm) latch bolt, battery operated Model(s) SAFFIRE LX, SAFFIRE EVO LX

Tubular type, with 12.7 mm (1/2 in.) latch bolts, battery operated Model(s) Confidant RFID, for use with 1/3 h hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height.

Tubular type, with 13 mm (1/2 in.) latch bolts, with 6 Vdc battery operated swinging fire doors up to 3/4 hr. "Saflok" Model(s) Confidant TL

Tubular type, with 13 mm (1/2 in.) latch bolts, with 6 Vdc battery operated swinging fire doors up to 1/3 hr. "Saflok" Model(s) Insync I Class, Insync L Class

Note - Models are evaluated in accordance with Standard, UL10C.

Last Updated on 2023-11-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."