

*Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).*

## Auxiliary Locks

### COMPANY

**dormakaba Canada Inc.**

105 Blvd Marcel-Laurin  
Saint-Laurent, QC H4N 2M3 Canada

R25978

**Auxiliary deadbolt locks** Model(s) Saffire LX-D, Saffire Evo LX-D, Saffire Evo LZ-D and Saffire Evo VR-D for use on swinging type fire door rated up to and including 3 hours

**Auxiliary locks of the tubular deadbolt type, for use on fire doors rated up to and including 20 minutes** Model(s) InSync D-Class

**Auxiliary locks of the tubular deadbolt type, for use on fire doors rated up to and including 20 minutes.** Model(s) E3XX, E4XX, E5XX

### Additionally Investigated to ANSI/UL 10C

**Auxiliary deadbolt locks** Model(s) EPLEX 1500 (a), EPLEX 1505 (a), NOVA-D (a), ORACODE 460 (a), ORACODE 480I (a)

(a) - For use on 3 hr hollow metal single swinging doors not exceeding 1220 mm in width by 2440 mm in height and swinging type fire doors rated up to and including 20 min.

Last Updated on 2023-11-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."