

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).

Accessories for Single-point Locks and Latches and Fire-exit Hardware Certified for Canada

COMPANY

dormakaba Canada Inc.

105 Blvd Marcel-Laurin
Saint-Laurent, QC H4N 2M3 Canada

R14199

Keylok assembly, "Solitaire" for the retro fitting of UL Listed cylindrical or mortise type single point locks as described in the manufacturer's installation instructions having a rating up to and including 3 hrs.

Keylock assembly, "Solitaire" Series 720 for the retrofitting of UL Listed fire exit hardware of the mortise, rim and vertical rod types, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "Millenium 530" for the retrofitting of UL Listed mortise type single point locks as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "Solitaire 710 II and 740" for the retrofitting of ULC Listed mortise type single point locks as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "Generation E-730, E-750 and 79 Series" for the retrofitting of UL Listed fire exit hardware of the mortise, rim and vertical rod types, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "EPLEX 7900 Series" for the retrofitting of UL Listed fire exit hardware of the mortise, rim and vertical rod types, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "SAFFIRE LX Series or SAFFIRE EVO LX" for the retrofitting of UL Listed fire exit hardware of the mortise, rim and vertical rod types, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "Generation E-630" for the retrofitting of UL Listed fire exit hardware of the mortise, rim and vertical rod types, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "Generation E-760" for the retrofitting of UL Listed mortise type single point locks as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "E-PLEX 2000 and 2400 Series", "E-PLEX Power Star 2000 and 2400 Series" and "PowerPlex 2000 and 2400 Series" for the retrofitting of UL Listed fire exit hardware, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Keylock assembly, "Model Confidant RFID" for the retrofitting of UL Listed fire exit hardware, as described in the manufacturer's installation instructions, having a rating up to and including 3 hrs.

Series 790, 79 RT, and 79 RT Plus proximity lock assemblies for the retrofitting of UL Listed single point locks of the mortise type manufactured by Onity under series designations HT, having a rating up to and including 3 hrs.

Lever handles and knobssets incorporating an electric card reader for the retrofitting of UL Listed mortise type single point locks having a rating up to and including 3 hrs. When this device employs lithium batteries, it shall be used on only wood core and wood or plastic covered composite type fire doors rated up to 45 minutes.

Exit device trim incorporating an electrical card reader for use as a retrofit for UL Listed fire exit hardware devices, Saflok MT RFID, Adese XT and Insync P Class.

Quantum Pixel+ Upgrade Kit for use in retrofitting of UL Listed Electrically Controlled Single-point Locks and Latches,d Model Quantum Pixel, and it shall be used with swinging wood, wood core doors for 1/3 hr., composite fire doors up to 1 hr. or hollow metal fire doors up to 3 hr.

Last Updated on 2024-10-02

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."